

Models

PC-300i – base model indoor plastic cabinet with plug-in 120VAC transformer, expands to 15 stations

PC-300 – base model outdoor locking plastic cabinet with 120VAC transformer, expands to 15 stations

PCM-300 – 3 station plug in module for use with any PC controller model

PCM-900 – 9 station plug in module for use with any PC controller model

Dimensions

- Indoor Model: 8.3" H x 9.6" W x 3.7" D
- Outdoor Model: 8.9" H x 9.9" W x 4.3" D

Operating Specifications

- Outdoor models, 120VAC transformer with internal junction box
- Indoor model, 120VAC two prong plug-in transformer
- Station output 24VAC .56 Amps
- Transformer output 24VAC 1.0 Amps
- Capable of operating equivalent of 3 solenoids simultaneously
- Operating Temperature: 0 - 150 degrees F
- NEMA rated outdoor cabinet
- UL Listed

Additional Features

- 4 start times per program for repeat watering needs
- Removable front panel for field or desktop programming; Panel interchangeable between indoor and outdoor units
- Up to six hours run time on all stations
- Automated chronological ordering of start times/start time stacking
- 365-day calendar with leap year intelligence
- Programmable event day off allows specific day(s) to be designated as always "off"
- Automatic station recognition when modules are inserted or removed
- Rain Sensor bypass switch compatible with micro-switch based sensors
- Programmable delay between stations 0-4 hours for well recovery or slow-closing valves
- Programmable rain delay for 1-7 days
- Compatible with Hunter's SRR and ICR remote control systems
- Built-in test program
- Central control compatible with Hunter Irrigation Management and Monitoring System™

Removable Face Plate: the power of desktop programming is in your hands

If you thought the only way to program a controller was to be standing right in front of it, think again. With the removable face plate on the Pro-C controller, simply detach the face plate of the unit and perform programming functions from a variety of different locations. Take the face plate with you and walk around the yard as you set the program (visiting each different zone as you program it). Program the controller from the comfort of your office before taking it to the customer's site for installation. Or, hand the panel over to your customer during installation and let them sample the programming features.

Modules: designed to make everything easier

It's designed to fit virtually any residential or light commercial need. It's designed for flexibility right at the job site. It's designed to keep an installer's inventory to a minimum.



What is it? It's the modular design of the Hunter Pro-C controller. Beginning with a 3-station base unit, the Pro-C can be expanded with up to 15 stations. Thus, a contractor no longer needs to stock eight different types of controllers (3-, 6-, 9-, 12- and 15-station units in both indoor and outdoor models)...he simply needs to keep on hand just four items (indoor and outdoor Pro-C base units and 3- or 9-station modules).

The flexibility to cover particular program needs

If your landscape is a particular one, with its own quirky requirements, the Pro-C is just the controller to handle that little prima donna. No other controller has more flexibility in its programming options. Need multiple daily waterings? How about 3 independent programs and 4 start times per program. Deep soaking needs? The Pro-C offers long station run times. Irrigation restrictions in your area? Choose from day of the week, interval watering or true odd/even scheduling. There's even an "event day off" feature that designates specified days of the week for non-watering (perfect for regular maintenance or special events).



Remote Compatible



Works with Weather Sensors

SPECIFICATION GUIDE

EXAMPLE: **PC - 300i**

MODEL	FEATURES
PC = Pro-C Controller	300i = 3-Station Base Unit Controller, Indoor Model, Plug-in Transformer, Expands to 15 Stations 300 = 3-Station Base Unit Controller, Outdoor Model, Internal Transformer, Expands to 15 Stations
PCM	300 = 3-Station Plug-in Module for use with any PC Controller Model 900 = 9-Station Plug-in Module for use with any PC Controller Model

PRO-C QUICK REFERENCE CHART

Desired Station Configuration	Order Base Unit	Plus Number of Modules	Specify as:
3 Zone	PC-300 or PC-300i	no module needed	PC-300i or PC-300
6 Zone	PC-300 or PC-300i	one PCM-300	PC-600i or PC-600
9 Zone	PC-300 or PC-300i	two PCM-300	PC-900i or PC-900
12 Zone	PC-300 or PC-300i	three PCM-300	PC-1200i or PC-1200
15 Zone	PC-300 or PC-300i	one PCM-300 and one PCM-900	PC-1500i or PC-1500